

# LED track light

IL-1975X

Catalog #		Type
Project		
Comments		Date
Prepared by		



## Specification:

Specially design for COB spot light,tigh & simplified,unique concept image guarantees and outsanding visual element..

Adopting ADC12 die-casting aluminium radiator with good heat dissipation.

PC driver box, Anti-glare plastic front cover design, die-casting aluminium body combination with high efficiency PC reflector to ensure that the light is more soft and comfortable.

3-phase track adaptor compatible with global Nordic track, single phase track compatible with HALO track or JUNO track system, easy to maintain and replace COB chip and driver.

Famous brand chip and cUL listed isolated power supply, safe and reliable.

Constant current and Dimming are available.

## Additional information:

- **Finish color:** White, Black, Silver grey
- **Socket type:** COB LED
- **Volts:** 120V / 277V
- **Maximum wattage:** 30 watt
- **Lumen:** 2400lm
- **PF:** >0.9
- **CRI:** 80+/90+
- **CCT:** 2700-6000K
- Dimmable Optional and Constant current
- **Switch:** hardwired
- **Reflector lens material and color:** frosted opal / clear
- **Beam angle:** 15D & 24D & 36D
- **Photometric:** IES file & optical sphere file are separate

## Mounting:

Track mounting for 3-phase track compatible with global universal track, Single-phase track compatible with Halo or JUNO track system

## Electrical:

Input Voltage: 120V/277V AC 50/60 Hz

## Location :

Dry


## Certificate:

ETL & cETL.

## Warranty:

Two or Five-years warranty.

## DIMENSIONS:



Accessories are available



Frosted



Clear



Honeycomb

